

## **Product Information**

Mod.R&S 06 | Rev.4 | Update 12/2018 | Page 1



## BRICK

Descripti	ion	Very thick PU plotter cut material, with polyester backing, available with matt or glossy finish. Despite the outstanding thickness, the material grants easy cutting,	Average thickness 1000 microns
		weeding and application and a high washing resistance. Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dye sublimated	Suggested cutting settings blade new at 60°
Usag	ge	N.B. : for a smooth application preheat the lower press plate for 15 seconds at 155°C.	pressure 150 gf speed 10 cm/sec
		Due to thickness it is possible to cut letters of 2 cm height minimum.	
		• Mirror cut the material	Transfer settings
		<ul> <li>Weed the exceeding material</li> </ul>	20 seconds at 155°C
		<ul> <li>Place the material on the garment with its polyester backing</li> </ul>	(310°F)
		<ul> <li>Heat apply at the conditions shown on the right</li> </ul>	medium pressure
		Remove the carrier cold	(3-4 bar)
		For glossy colours GOLD and SILVER only:	
		<ul> <li>Heat apply at the conditions shown on the right</li> </ul>	
		• Remove the carrier cold	
		<ul> <li>Cover with silicon paper or teflon and press again for 5 seconds</li> </ul>	
Washin	ng	Wait at least 24 hours from application before washing.	Washing temperature
	_	Washing resistance up to 60°C, best inside-out.	607
		Do not use bleach or other aggressive chemical agents.	
		Not suitable for dry cleaning	Dry cleaning
		Suitable for tumble dry, cotton program	$\otimes$
		The product is REACH compliant	Tumble dryer
		The product is certified Öko-Tex <sup>®</sup> Standard 100 Class II	$\odot$
		OEKO-TEX®	
	N.B.	All information here contained are based on our experience.	
		We recommend to perform a test before starting standard production.	
		For best results we suggest to store the product away from sunlight and dust, in	

We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations.

Updated versions are available on our website www.siser.com For further information, please contact our Sales Office. Thank you



Siser s.r.l. Viale della Tecnica, 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it - <u>www.siser.com</u> r.e.a. vi 171856 reg. imp. vi n° 14971 c.s. € 103.300 i.v. p.iva 01591490246